

## POWER TRAX HD (FL) - Технические спецификации



### Description

POWER TRAX HD — диагональные шины премиум-класса для промышленных вилочных погрузчиков. Глубокий протектор, утолщенная боковая стенка и прочный корпус гарантируют исключительную долговечность, а также минимизируют риск проколов и случайных повреждений. Благодаря отличной устойчивости к порезам, расщеплению и разрывам эти шины подходят для шероховатой и твердой бетонной поверхности. Специально разработанная защита обода предотвращает проколы и повреждение колеса у борта.

### UM

US Standard

### Construction

 BIAS

### Machinery

Производство: Вилочный погрузчик

Version	STANDARD
Type	TT
Tyre Size	10.00L - 15 (36 X 11 - 15)

## Dimensions US Standard

Usa code	94007646
Ply Rating	16
Section Width (inch)	11.2
Overall Diameter (inch)	36.1
Rim Rec	7.50 BD
Rim Alt	7.5

## Load capacity (lbs)

mph / psi	131
15 LOAD WHEEL	12180
15 STEER WHEEL	9370
5 OTHER VEHICLES	12180
15 OTHER VEHICLES	9370
STATIC SIDE LOADER	14155

Printed on 26.04.2024 19:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..