

POWER TRAX HD (FL) - Технические спецификации



Description

POWER TRAX HD — диагональные шины премиум-класса для промышленных вилочных погрузчиков. Глубокий протектор, утолщенная боковая стенка и прочный корпус гарантируют исключительную долговечность, а также минимизируют риск проколов и случайных повреждений. Благодаря отличной устойчивости к порезам, расщеплению и разрывам эти шины подходят для шероховатой и твердой бетонной поверхности. Специально разработанная защита обода предотвращает проколы и повреждение колеса у борта.

UM

US Standard

Construction

 BIAS

Machinery

Производство: Вилочный погрузчик

Version	STANDARD
Type	TT
Tyre Size	27 X 10 - 12 (250/75 - 12)

Dimensions US Standard

Usa code	94007769
Ply Rating	20
Section Width (inch)	10
Overall Diameter (inch)	27.2
Rim Rec	8.00 G

ECE

Load capacity (lbs)

mph / psi	145
15 LOAD WHEEL	10175
15 STEER WHEEL	7825
5 OTHER VEHICLES	10175
15 OTHER VEHICLES	7825
STATIC SIDE LOADER	11815

Printed on 26.04.2024 20:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..