

## POWER TRAX HD (FL) - Технические спецификации



### Description

POWER TRAX HD — диагональные шины премиум-класса для промышленных вилочных погрузчиков. Глубокий протектор, утолщенная боковая стенка и прочный корпус гарантируют исключительную долговечность, а также минимизируют риск проколов и случайных повреждений. Благодаря отличной устойчивости к порезам, расщеплению и разрывам эти шины подходят для шероховатой и твердой бетонной поверхности. Специально разработанная защита обода предотвращает проколы и повреждение колеса у борта.

### UM

US Standard

### Construction

 BIAS

### Machinery

Производство: Вилочный погрузчик

Version	STANDARD
Type	TT
Tyre Size	28 X 12.5 - 15

## Dimensions US Standard

Usa code	94048649
Ply Rating	24
Section Width (inch)	12
Overall Diameter (inch)	27.8
Rim Rec	9.75 BD

ECE

## Load capacity (lbs)

	mph / psi	145
15 LOAD WHEEL		10460
15 STEER WHEEL		8045
5 OTHER VEHICLES		10460
15 OTHER VEHICLES		8045
STATIC SIDE LOADER		12145

Printed on 26.04.2024 21:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..