

POWERTRAILER SR 331 - Технические спецификации



Description

POWERTRAILER SR 331 — новая радиальная шина с металлокордом от BKT, разработанная специально для прицепов и автоцистерн. POWERTRAILER SR 331 подходит для эксплуатации как в полевых условиях, так и на дорогах с покрытием: шина отличается хорошей проходимостью и превосходным сцеплением с асфальтом или другими твердыми поверхностями. Конструкция с цельным металлокордом обеспечивает высокую грузоподъемность, исключительную устойчивость каркаса и увеличенный срок службы. Особое устройство боковины с выступающим ребром гарантирует надежную защиту при ударах и трении, а шестигранный борт с усиленным бортовым кольцом обеспечивает идеальную посадку шины на колесный диск. Кроме того, многоблочный рисунок протектора способствует снижению сопротивления качению, равномерному распределению давления в пятне контакта и повышению плавности хода. Благодаря всем этим особенностям POWERTRAILER SR 331 — залог топливной экономичности и ездового комфорта.

UM

International Standard

Construction

 RADIAL

Machinery

Сельское хозяйство: Автоцистерна • Прицеп

Version	IMPLEMENT
Type	TL
Tyre Size	560/60 R 22.5
LI/SS	165 D

Dimensions International Standard

Overall Width (mm)	555
Overall Diameter (mm)	1245
Static Loaded Radius (mm)	565
Rolling Circumference (mm)	3775
SRI (mm)	600
Rim Rec	AG 16.00
Rim Alt	17.00 ; AG18.00
ECE	E11-106R-0010087

Load capacity (Kg)

km/h / bar	3.2	3.6	4	4.5	5
10	6860	7505	8255	8810	9270
25	6020	6590	7245	7735	8135
40	5180	5670	6235	6655	7005
50	4610	5045	5550	5925	6230
65	3810	4170	4585	4895	5150
70	3465	3795	4170	4455	4685

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 07.12.2024 20:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..