

PRO RIB F2M - Технические спецификации



Description

PRO RIB F2M — это сельскохозяйственные шины для обработки почвы с использованием тракторов с двумя ведущими колесами. Они особенно подойдут для любой техники, от которой требуется высокий уровень управляемости.

UM

International Standard

Construction

BIAS

Machinery

Сельское хозяйство: Трактор 2WD

Производство: Прицеп

Version	STANDARD
Type	TL
Tyre Size	11L - 15 SL
LI/SS	106 A8

Dimensions International Standard

Ply Rating	8
Section Width (mm)	280
Overall Diameter (mm)	795
Static Loaded Radius (mm)	370
Rolling Circumference (mm)	2370
Rim Rec	8 LB
Rim Alt	10 LB
ECE	E11-106R-004588
TRA Code	F2M

Load capacity (Kg)

km/h / bar	3.00
40	950

Printed on 10.04.2024 14:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..