

PUDDLE SPECIAL (A) - Технические спецификации



Description

PUDDLE SPECIAL — это сельскохозяйственные шины R-2, специально предназначенные для техники, работающей на рисовых плантациях. Очень глубокий рисунок протектора и специальные грунтозацепы обеспечивают наилучшее сцепление и превосходную тягу даже на влажной и мягкой почве. Широкая часть грунтозацепов по центру позволяет эксплуатировать шины и на дорогах, а также обеспечивает превосходные сервисные показатели. Кроме того, шины PUDDLE SPECIAL имеют превосходные свойства самоочистки и высокую долговечность.

UM

International Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Трактор-тягач

Version	STANDARD
Type	TL
Tyre Size	11 - 32
LI/SS	111 A2

Dimensions International Standard

Ply Rating	6
Section Width (mm)	305
Overall Diameter (mm)	1465
Static Loaded Radius (mm)	702
Rolling Circumference (mm)	4384
Rim Rec	W 10
Rim Alt	W 9
ECE	E11-106R-004096
TRA Code	R2+

Load capacity (Kg)

km/h / bar	1.60
10	1080

Printed on 26.04.2024 6:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..