

## PUDDLE SPECIAL (A) - Технические спецификации



### Description

PUDDLE SPECIAL — это сельскохозяйственные шины R-2, специально предназначенные для техники, работающей на рисовых плантациях. Очень глубокий рисунок протектора и специальные грунтозацепы обеспечивают наилучшее сцепление и превосходную тягу даже на влажной и мягкой почве. Широкая часть грунтозацепов по центру позволяет эксплуатировать шины и на дорогах, а также обеспечивает превосходные сервисные показатели. Кроме того, шины PUDDLE SPECIAL имеют превосходные свойства самоочистки и высокую долговечность.

### UM

US Standard

### Construction

 BIAS

### Machinery

Сельское хозяйство: Трактор-тягач

Version	STANDARD
Type	TT
Tyre Size	12.4 - 28
LI/SS	137 A2

## Dimensions US Standard

Usa code	94059461
Ply Rating	12
Section Width (inch)	12.8
Overall Diameter (inch)	54.5
Static Loaded Radius (inch)	25.6
Rolling Circumference (inch)	160.1
Rim Rec	W 11
Rim Alt	W 10
TRA Code	R2+

## Load capacity (lbs)

mph / psi	52
5	5080

Printed on 12.08.2024 14:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..