

PUDDLE SPECIAL (B) - Технические спецификации



Description

PUDDLE SPECIAL — это сельскохозяйственные шины R-2, специально предназначенные для техники, работающей на рисовых плантациях. Очень глубокий рисунок протектора и специальные грунтозацепы обеспечивают наилучшее сцепление и превосходную тягу даже на влажной и мягкой почве. Широкая часть грунтозацепов по центру позволяет эксплуатировать шины и на дорогах, а также обеспечивает превосходные сервисные показатели. Кроме того, шины PUDDLE SPECIAL имеют отличные свойства самоочистки и высокую долговечность.

UM

International Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Опрыскиватель

Version	STANDARD
Type	TT
Tyre Size	120/90 - 26
LI/SS	90 A2

Dimensions International Standard

Ply Rating	6
Section Width (mm)	127
Overall Diameter (mm)	940
Static Loaded Radius (mm)	448
Rolling Circumference (mm)	2847
Rim Rec	4 JA
ECE	E11-106R-005236

Load capacity (Kg)

km/h / bar	3.00
10	600

Printed on 25.04.2024 9:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..