

PUDDLE SPECIAL (B) - Технические спецификации



Description

PUDDLE SPECIAL — это сельскохозяйственные шины R-2, специально предназначенные для техники, работающей на рисовых плантациях. Очень глубокий рисунок протектора и специальные грунтозацепы обеспечивают наилучшее сцепление и превосходную тягу даже на влажной и мягкой почве. Широкая часть грунтозацепов по центру позволяет эксплуатировать шины и на дорогах, а также обеспечивает превосходные сервисные показатели. Кроме того, шины PUDDLE SPECIAL имеют отличные свойства самоочистки и высокую долговечность.

UM

US Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Опрыскиватель

Version	STANDARD
Type	TL
Tyre Size	120/90 - 26
LI/SS	90 A2

Dimensions US Standard

Usa code	94059638
Ply Rating	6
Section Width (inch)	5
Overall Diameter (inch)	37
Static Loaded Radius (inch)	17.6
Rolling Circumference (inch)	112.1
Rim Rec	4 JA
ECE	E11-106R-005236

Load capacity (lbs)

mph / psi	44
5	1320

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 07.10.2024 1:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..