

RIB 774 (A) - Технические спецификации



Description

RIB 774 (A) — низкопрофильные сельскохозяйственные шины с высокой грузоподъемностью и длительным сроком службы. Они подходят для пресс-подборщиков и прицепов, используемых для уборочных работ и грузоперевозок.

UM

US Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Пресс-подборщик • Сенокосилка •
Прицеп

Version	STANDARD
Type	TT
Tyre Size	200/60 - 14.5
LI/SS FREE ROLLING	113 A8

Dimensions US Standard

Usa code	94010981
Ply Rating	14
Section Width (inch)	8.3
Overall Diameter (inch)	24
Static Loaded Radius (inch)	11.3
Rolling Circumference (inch)	74.3
Rim Rec	AG 6.75
ECE	E11-106R-003608

Load capacity (lbs)

mph / psi	102
5 FR	3350
15 FR	3020
20 FR	2840
25 FR	2540

Printed on 23.04.2024 23:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..