

RIB 774 (A) - Технические спецификации



Description

RIB 774 (A) — низкопрофильные сельскохозяйственные шины с высокой грузоподъемностью и длительным сроком службы. Они подходят для пресс-подборщиков и прицепов, используемых для уборочных работ и грузоперевозок.

UM

US Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Пресс-подборщик • Сенокосилка •
Прицеп

| | |
|--------------------|---------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 250/65 - 14.5 |
| LI/SS FREE ROLLING | 124 A8 |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94027255 |
| Ply Rating | 14 |
| Section Width (inch) | 10 |
| Overall Diameter (inch) | 27.2 |
| Static Loaded Radius (inch) | 11.9 |
| Rolling Circumference (inch) | 77.9 |
| Rim Rec | AG 8.00 |
| Rim Alt | 6.75 |
| ECE | E11-106R-003374 |

Load capacity (lbs)

| mph / psi | 80 |
|-----------|------|
| 5 FR | 4940 |
| 15 FR | 4200 |
| 20 FR | 3950 |
| 25 FR | 3530 |

Printed on 23.04.2024 20:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..