

## RIB 900 - Технические спецификации



### Description

RIB 900 — это шины для сельскохозяйственной техники, прицепов и пресс-подборщиков, используемых для перевозок, обработки почвы и уборочных работ. Они обладают долгим сроком службы и обеспечивают высокую грузоподъемность.

### UM

International Standard

### Construction

 BIAS

### Machinery

Сельское хозяйство: Пресс-подборщик • Сенокосилка •  
Сельскохозяйственное оборудование • Прицеп

Version	STANDARD
Type	TL
Tyre Size	400/60 - 15.5
LI/SS FREE ROLLING	147 A8

## Dimensions International Standard

Ply Rating	16
Section Width (mm)	405
Overall Diameter (mm)	875
Static Loaded Radius (mm)	380
Rolling Circumference (mm)	2564
Rim Rec	AG 13.00
ECE	E4-106R-001548

## Load capacity (Kg)

	km/h / bar	4.00
	10 FR	4305
	25 FR	3660
	30 FR	3445
	40 FR	3075

Printed on 09.05.2024 7:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..