

RIB TRAILER - Технические спецификации



Description

RIB TRAILER — это диагональная шина, разработанная специально для сельскохозяйственной техники на дороге и в поле, особенно для жатвенных машин. Рисунок протектора с четырьмя ребрами оптимизирует распределение нагрузки, а прочный каркас гарантирует стойкость к повреждению стерней. Шина RIB TRAILER изготавливается из специальной резиновой смеси, обеспечивающей долгий срок службы благодаря износостойкости.

UM

International Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Сельскохозяйственное оборудование

Version	STANDARD
Type	TT
Tyre Size	6.00 - 16
LI/SS	94 A6

Dimensions International Standard

Ply Rating	8
Section Width (mm)	170
Overall Diameter (mm)	735
Rim Rec	4.50 E
Rim Alt	4.00 E ; 5 K ; 5.00 F

Load capacity (Kg)

km/h / bar	4.50
30	670

Printed on 17.04.2024 18:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..