

RIDEMAX FL 699 - Технические спецификации



Description

RIDEMAX FL 699 — шины BKT для прицепов и автоцистерн, используемых на дорогах. Эти полностью стальные шины отличаются высокой ходимостью и долговечностью. Усиленные борта обеспечивают лучшую устойчивость даже на высокой скорости. Несмотря на то, что новые шины RIDEMAX FL 699 разрабатывались для преимущественного использования на дорогах (90 % времени эксплуатации), например, для перевозок в фермерском хозяйстве, они также демонстрируют превосходные характеристики в поле. При разработке шин особое внимание уделялось грузоподъемности, так как этот ключевой фактор может снизить количество поездок, что, в свою очередь, приведет к снижению расходов. Хорошие новости для фермеров, которым прицеп доставляет неудобства при вождении: RIDEMAX FL 699 гарантирует непревзойденный комфорт во время движения, обеспечивая безопасность и отличную управляемость.

UM

US Standard

Construction

 RADIAL

Machinery

Сельское хозяйство: Автоцистерна • Прицеп

Version	STANDARD
Type	TL
Tyre Size	24 R 20.5
LI/SS	176 F

Dimensions US Standard

Usa code	94063680
Ply Rating	16
Overall Width (inch)	23.2
Overall Diameter (inch)	53.9
Static Loaded Radius (inch)	24.1
Rolling Circumference (inch)	164
Rim Rec	18.00
ECE	E11-54R-0017755

Load capacity (lbs)

mph / psi	58	73	87
25-30	11900	14220	16450
35-50	11330	13540	15660

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 11.05.2025 9:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..