

RIDEMAX IT 696 - Технические спецификации



Description

Шины RIDEMAX IT 696 с уникальным рисунком протектора и широким пятном контакта обеспечивают превосходное сцепление с дорожным покрытием даже в условиях зимы. Эти шины лучше всего подойдут для техники, используемой для грузовых перевозок и муниципальных/ремонтных работ, в особенности благодаря их быстроходности и прочному каркасу. Рисунок протектора был специально разработан для работы в условиях больших нагрузок: он обеспечивает низкое сопротивление качению, что приводит к снижению расхода топлива и отличной устойчивости.

UM

International Standard

Construction

 RADIAL

Machinery

Сельское хозяйство: Трактор-тягач

| | |
|-----------|--------------------------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 440/80 R 30 IND (16.9 R 30) |
| LI/SS | 157 A8/153 D |

Dimensions International Standard

| | |
|----------------------------|----------------|
| Section Width (mm) | 441 |
| Overall Diameter (mm) | 1466 |
| Static Loaded Radius (mm) | 668 |
| Rolling Circumference (mm) | 4456 |
| SRI (mm) | 700 |
| Rim Rec | W 14 L |
| Rim Alt | W 15 L |
| ECE | E4-106R-002297 |

Load capacity (Kg)

| km/h / bar | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 |
|------------|------|------|------|------|------|------|
| 65 | 1715 | 2115 | 2480 | 2885 | 3250 | 3650 |
| 50 | 1825 | 2250 | 2640 | 3065 | 3455 | 3880 |
| 40 | 1940 | 2395 | 2805 | 3260 | 3670 | 4125 |
| 30 | 2020 | 2495 | 2925 | 3395 | 3825 | 4300 |

Printed on 02.03.2024 22:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..