

RM 500 - Технические спецификации



Description

RM 500 — это радиальные шины со стальным брекером, подходящие для уборочной техники. Они обладают прочным каркасом и специальным рисунком протектора, что гарантирует высокую грузоподъемность и превосходную устойчивость к порезам и разрывам. Благодаря большому пятну контакта шины RM 500 обеспечивают превосходное распределение давления по земле, снижая уплотнение почвы и демонстрируя великолепную тягу.

UM

US Standard

Construction

 RADIAL

Machinery

Сельское хозяйство: Комбайн

| | |
|--------------------|-----------------|
| Version | STEEL BELTED |
| Type | TL |
| Tyre Size | 500/85 R 24 |
| LI/SS | 182 A8 / 170 A8 |
| LI/SS DRIVE WHEEL | 170 A8 |
| LI/SS FREE ROLLING | 182 A8 |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94075522 |
| Section Width (inch) | 20.5 |
| Overall Diameter (inch) | 57.5 |
| Static Loaded Radius (inch) | 24.5 |
| Rolling Circumference (inch) | 172.5 |
| Rim Rec | W 16 L |
| Rim Alt | W 15 L |
| ECE | E11-106R-005991 |

Load capacity (lbs)

| mph / psi | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 |
|-----------------|------|------|-------|-------|-------|-------|-------|-------|
| 25 Free Rolling | 7870 | 9560 | 11060 | 12740 | 14430 | 15550 | 17050 | 18740 |
| 25 Drive Wheel | 5560 | 6750 | 7800 | 8990 | 10180 | 10980 | 12040 | 13230 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 08.12.2024 16:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..