

RM 500 - Технические спецификации



Description

RM 500 — это радиальные шины со стальным брекером, подходящие для уборочной техники. Они обладают прочным каркасом и специальным рисунком протектора, что гарантирует высокую грузоподъемность и превосходную устойчивость к порезам и разрывам. Благодаря большому пятну контакта шины RM 500 обеспечивают превосходное распределение давления по земле, снижая уплотнение почвы и демонстрируя великолепную тягу.

UM

US Standard

Construction

 RADIAL

Machinery

Сельское хозяйство: Комбайн

Version	STEEL BELTED
Type	TL
Tyre Size	600/65 R 28
LI/SS	168 A8 / 156 A8
LI/SS DRIVE WHEEL	156 A8
LI/SS FREE ROLLING	168 A8

Dimensions US Standard

Usa code	94063666
Section Width (inch)	23.2
Overall Diameter (inch)	58.5
Static Loaded Radius (inch)	25.2
Rolling Circumference (inch)	170.9
Rim Rec	W 18 L
Rim Alt	W 20 L
ECE	E11-106R-005993

Load capacity (lbs)

mph / psi	12	16	17	23	29
25 Free Rolling	6790	7780	8770	10630	12350
25 Drive Wheel	4850	5560	6260	7580	8820

Printed on 26.04.2024 16:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..