

ROCK GRIP E4 - Загрузить лист технических данных



Description

ROCK GRIP (E-4) - это диагональные шины, специально созданные для грузовиков, которые используются для горных работ и разработок карьеров. Если условия вашей работы требуют от шины высокой степени термостойкости и защиты от порезов, ROCK GRIP станет вашим надежным партнером.

UM

US Standard

Construction

 BIAS

Machinery

Производство: Самосвал с жесткой рамой

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
14.00 - 25	STANDARD	94042210	E4	32	10.00/2.0		14.8	55.5	25.6	164.3	TL
14.00 - 25	STANDARD	94041879	E4	24	10.00/2.0		14.8	55.5	25.6	164.3	TL
14.00 - 25	STANDARD	94039746	E4	28	10.00/1.5		14.8	55.5	25.6	164.3	TL
14.00 - 25	STANDARD	94039753	E4	28	10.00/1.5		14.8	55.5	25.6	164.3	TT
14.00 - 25	STANDARD	94041893	E4	28	10.00/2.0		14.8	55.5	25.6	164.3	TL
14.00 - 25	STANDARD	94042203	E4	28	10.00/2.0		14.8	55.5	25.6	164.3	TT
14.00 - 25	STANDARD	94039760	E4	32	10.00/1.5		14.8	55.5	25.6	164.3	TL
14.00 - 25	STANDARD	94039722	E4	24	10.00/1.5		14.8	55.5	25.6	164.3	TL
14.00 - 25	STANDARD	94041886	E4	24	10.00/2.0		14.8	55.5	25.6	164.3	TT
14.00 - 25	STANDARD	94039739	E4	24	10.00/1.5		14.8	55.5	25.6	164.3	TT
16.00 - 25	STANDARD	94027651	E4	28	11.25/2.0	13.00/2.0	18.5	60	27.5	177.7	TL
16.00 - 25	STANDARD	94025879	E4	32	11.25/2.0	13.00/2.0	18.5	60	27.5	177.7	TL
18.00 - 25	STANDARD	94015528	E4	40	13.00/2.5	15.00/2.5	20.1	65	29.6	192.3	TL
18.00 - 25	STANDARD	94015498	E4	32	13.00/2.5	15.00/2.5	20.1	65	29.6	192.3	TL
18.00 - 25	STANDARD	94015504	E4	36	13.00/2.5	15.00/2.5	20.1	65	29.6	192.3	TL
18.00 - 25	STANDARD	94015511	E4	40	13.00/2.5	15.00/2.5	20.1	65	29.6	192.3	TT
18.00 - 25	STANDARD	94015474	E4	24	13.00/2.5	15.00/2.5	20.1	65	29.6	192.3	TT
18.00 - 25	STANDARD	94015481	E4	32	13.00/2.5	15.00/2.5	20.1	65	29.6	192.3	TT
18.00 - 33	CUT RESISTANT COMPOUND	94048762	E4	40	13.00/2.5		20.1	74.3	34.2	219.9	TL
18.00 - 33	CUT RESISTANT COMPOUND	94048465	E4	36	13.00/2.5		20.1	74.3	34.2	219.9	TL
18.00 - 33	STANDARD	94015535	E4	36	13.00/2.5		20.1	74.3	34.2	219.9	TT
18.00 - 33	STANDARD	94015542	E4	36	13.00/2.5		20.1	74.3	34.2	219.9	TL
18.00 - 33	STANDARD	94015559	E4	40	13.00/2.5		20.1	74.3	34.2	219.9	TT
18.00 - 33	STANDARD	94015566	E4	40	13.00/2.5		20.1	74.3	34.2	219.9	TL
18.00 - 33	STANDARD	94015573	E4	44	13.00/2.5		20.1	74.3	34.2	219.9	TL
21.00 - 35	CUT RESISTANT COMPOUND	94048779	E4	40	15.00/3.0		22.8	80.3	37.1	238.9	TL
21.00 - 35	CUT RESISTANT COMPOUND	94067343	E4	36	15.00/3.0		22.8	80.3	37.1	238.9	TL
21.00 - 35	STANDARD	94015580	E4	36	15.00/3.0		22.8	80.3	37.1	238.9	TL
21.00 - 35	STANDARD	94015597	E4	40	15.00/3.0		22.8	80.3	37.1	238.9	TL
24.00 - 35	CUT RESISTANT COMPOUND	94044702	E4	48	17.00/3.5		25.8	86.2	39.5	255.2	TL
24.00 - 35	STANDARD	94015603	E4	48	17.00/3.5		25.8	86.2	39.5	255.2	TL
24.00 - 49	CUT RESISTANT COMPOUND	94048496	E4	48	17.00/3.5		25.8	99.6	46.6	295.2	TL
24.00 - 49	STANDARD	94026548	E4	42	17.00/3.5		25.8	99.6	46.6	295.2	TL
24.00 - 49	STANDARD	94025893	E4	48	17.00/3.5		25.8	99.6	46.6	295.2	TL
27.00 - 49	CUT RESISTANT COMPOUND	94044597	E4	48	19.50/4.0		29.1	106.1	49.3	314.4	TL
27.00 - 49	CUT RESISTANT COMPOUND	94067299	E4	54	19.50/4.0		29.1	106.1	49.3	314.4	TL
27.00 - 49	STANDARD	94035281	E4	54	19.50/4.0		29.1	106.1	49.3	314.4	TL
27.00 - 49	STANDARD	94026555	E4	48	19.50/4.0		29.1	106.1	49.3	314.4	TL
30.00 - 51	CUT RESISTANT COMPOUND	94044603	E4	52	22.00/4.5		32.7	114.6	53.1	339.2	TL
30.00 - 51	STANDARD	94029228	E4	46	22.00/4.5		32.7	114.6	53.1	339.2	TL
30.00 - 51	STANDARD	94029235	E4	52	22.00/4.5		32.7	114.6	53.1	339.2	TL

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..