

ROCK GRIP IND4 (ECH) - Технические спецификации



Description

ROCK GRIP PORT INDUSTRIAL IND-4 (ECH) — это диагональная шина для погрузчиков пустых контейнеров, используемых в различных сферах, включая промышленные предприятия и металлургические заводы. Специальные резиновые смеси ROCK GRIP гарантируют особую стойкость к теплообразованию, а также отличные устойчивость и прочность.

UM

International Standard

Construction

 BIAS

Machinery

Производство: Погрузчик пустых контейнеров

Version	PORT INDUSTRIAL
Type	TL
Tyre Size	14.00 - 24

Dimensions International Standard

Ply Rating	32
Overall Width (mm)	375
Overall Diameter (mm)	1410
Static Loaded Radius (mm)	647
Rolling Circumference (mm)	4173
Rim Rec	10.00 WA
Rim Alt	10.00 VA
TRA Code	IND4

Load capacity (Kg)

km/h / bar	10.00
10	14175

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 13.10.2024 8:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..