

ROCK GRIP L4 - Технические спецификации



Description

ROCK GRIP (L-4) - это диагональные шины для колесных автопогрузчиков, работающих в условиях больших нагрузок и на сложных поверхностях. Специально разработанная резиновая смесь их протектора значительно повышает устойчивость к порезам и разрывам, что в целом уменьшает время простоя оборудования. Глубокий рисунок протектора (L-4) гарантирует увеличенный срок службы шины.

UM

International Standard

Construction

 BIAS

Machinery

Производство: Бульдозер • Погрузчик

Version	STANDARD
Type	TL
Tyre Size	14.00 - 25

Dimensions International Standard

Ply Rating	28
Overall Width (mm)	375
Overall Diameter (mm)	1410
Static Loaded Radius (mm)	649
Rolling Circumference (mm)	4173
Rim Rec	10.00/1.5
TRA Code	L4

Load capacity (Kg)

km/h / bar	9.25
10	10000

Printed on 27.04.2024 10:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..