

ROCK GRIP (T) - Загрузить лист технических данных



Description

ROCK GRIP (E-4) лучше всего подходят для грузовиков и карьерной техники горнодобывающей отрасли, где требуется перевозка больших грузов на небольшие расстояния. Специальная резиновая смесь протектора обеспечивает высокое сопротивление проколам и порезам даже при работе на самом грубом грунте. Шины ROCK GRIP (E-4) отличаются исключительными тяговыми характеристиками и долгим сроком службы.

UM

US Standard

Construction

 BIAS

Machinery

Производство: Дорожный/внедорожный грузовик •
Самосвал с жесткой рамой

| SIZE | Version | USACode | PR | RIM REC | RIM ALT | OW | OD | SLR | RC | Type |
|------------|----------|----------|----|---------|---------|------|------|------|-------|------|
| 10.00 - 20 | STANDARD | 94050802 | 18 | 7.5 | 7.0 | 11 | 42.9 | 0 | 0 | TT |
| 11.00 - 20 | STANDARD | 94062416 | 18 | 8.0 | 7.5 | 11.8 | 44.7 | 0 | 0 | TT |
| 12.00 - 20 | STANDARD | 94070114 | 20 | 8.5 | 8.0 | 12.4 | 46.1 | 0 | 0 | TT |
| 12.00 - 24 | STANDARD | 94035601 | 18 | 8.5 | 8.0 | 12.4 | 49.8 | 23.4 | 147.8 | TT |
| 12.00 - 24 | STANDARD | 94035755 | 20 | 8.5 | 8.0 | 12.4 | 49.8 | 23.4 | 147.8 | TT |

Printed on 23.04.2024 22:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..