

ROCK STAR IND4 - Технические спецификации



Description

Шина ROCK STAR PORT IND-4 специально разработана для погрузчиков пустых контейнеров и вилочных погрузчиков. Помимо превосходной тяги, уникальная резиновая смесь придает шине великолепную стойкость к порезам и сколам. ROCK STAR PORT IND-4 отличается выдающейся грузоподъемностью и превосходной прочностью.

UM

International Standard

Construction

 BIAS

Machinery

Производство: Погрузчик пустых контейнеров • Вилочный погрузчик

Version	PORT INDUSTRIAL
Type	TT
Tyre Size	14.00 - 24

Dimensions International Standard

Ply Rating	28
Overall Width (mm)	390
Overall Diameter (mm)	1425
Static Loaded Radius (mm)	635
Rolling Circumference (mm)	4350
Rim Rec	10.00 WA
Rim Alt	10.00 VA
TRA Code	IND4

Load capacity (Kg)

km/h / bar	10.00
10	13500

Printed on 26.04.2024 17:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..