

RT 857 - Технические спецификации



Description

TR 857 — это шины для техники, используемой для обработки почвы. Прочный каркас обеспечивает превосходные тяговые характеристики и долгий срок службы. Протектор из специальной резиновой смеси гарантирует прочность шин при движении по пожнивным остаткам и высокую устойчивость к порезам и разрывам.

UM

US Standard

Construction

 RADIAL

Machinery

Сельское хозяйство: Трактор-тягач

| | |
|-----------|----------------------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 380/85 R 24 (14.9 R 24) |
| LI/SS | 131 A8/B |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94053773 |
| Section Width (inch) | 15 |
| Overall Diameter (inch) | 49.4 |
| Static Loaded Radius (inch) | 22.3 |
| Rolling Circumference (inch) | 148.9 |
| Rim Rec | W 12 |
| Rim Alt | W 13 ; W 11 |
| ECE | E11-106R-002977 |
| TRA Code | R1 |

Load capacity (lbs)

| mph / psi | 9 | 12 | 15 | 17 | 20 | 23 |
|-----------|------|------|------|------|------|------|
| 30 | 2370 | 2760 | 3140 | 3530 | 3910 | 4300 |
| 25 | 2370 | 2760 | 3140 | 3530 | 3910 | 4300 |
| 20 | 2540 | 2950 | 3370 | 3780 | 4200 | 4610 |
| 5 LT | 3170 | 3690 | 4210 | 4730 | 5250 | 5760 |
| 5 HT | 2540 | 2950 | 3370 | 3780 | 4200 | 4610 |

Printed on 17.04.2024 22:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..