

SAND KING - Технические спецификации



Description

SAND KING - это шины с блочным рисунком протектора, специально разработанные для прицепов, которые используются для грузовых перевозок. Они обеспечивают превосходную тягу на песчаных поверхностях и идеальный контакт с поверхностью.

UM

US Standard

Construction



Machinery

Производство: Прицеп

Version	STANDARD
Туре	тт
Tyre Size	425 / 90 D - 21 (15.00 - 21)

Dimensions US Standard

Usa code	94068814
Ply Rating	18
Section Width (inch)	16.5
Overall Diameter (inch)	52.4
Rim Rec	11.25

Load capacity (lbs)

mph / psi	95
40	10900

Printed on 13.03.2024 10:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..