

SAND STAR - Технические спецификации



Description

SAND STAR - это шины с блочным рисунком протектора, специально разработанные для прицепов. Они обеспечивают превосходную тягу на песчаных поверхностях и идеальный контакт с поверхностью. Шины также минимизируют уплотнение почвы при работе техники.

UM

International Standard

Construction

 BIAS

Machinery

Производство: Прицеп

Version	STANDARD
Type	TL
Tyre Size	9.00 - 13
LI/SS	119 A8

Dimensions International Standard

Ply Rating	10
Section Width (mm)	245
Overall Diameter (mm)	784
Rim Rec	5.50 F
Rim Alt	5.50 WB
ECE	E11-106R-005263

Load capacity (Kg)

km/h / bar	3.25
40 FR LLV	1360

Printed on 20.04.2024 4:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..