SIERRA MAX PRO - Технические спецификации

Description

SIERRA MAX PRO — это идеальная шина BKT для техники высокой проходимости, в том числе для совместной работы. Радиальная конструкция и особое увеличенное пятно контакта обеспечивают более комфортное движение и оптимизированную тягу во всех направлениях. Специальные крепкие грунтозацепы специально разработаны для великолепной тяги и надежного сцепления с поверхностью. Эти характеристики гарантируют непревзойденный комфорт во время движения, обеспечивая безопасность и управляемость. Шина SIERRA MAX PRO отличается великолепными характеристиками на любом типе покрытия: от плотного грунта до мягкой почвы.

UM

US Standard

Construction

RADIAL

Machinery

Сельское хозяйство: вездеход

Version	STANDARD
Type	
Tyre Size	AT 27 X 11 R 14
LI/SS	56 N

Dimensions US Standard

Usa code	94066155
Section Width (inch)	11.2
Overall Diameter (inch)	27.9
Static Loaded Radius (inch)	13.2
Rolling Circumference (inch)	84.4
Rim Rec	9.00
Star Rating	***
ECE	E11-75R-005098

Load capacity (lbs)

mph / psi	18
87	495

Printed on 26.04.2024 19:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..