

SIERRA MAX - Технические спецификации



Description

SIERRA MAX — это шины BKT, которые подходят для внедорожной техники и могут эксплуатироваться как на бездорожье, так и при выполнении садово-огородных работ. Благодаря радиальной конструкции они обеспечивают более плавный и комфортный ход по суровой труднопроходимой местности, включая, например, пустыни или грязные и каменистые поверхности. Особый рисунок протектора и пятно контакта увеличенной ширины гарантируют отличную передачу тягового усилия как в продольном, так и в поперечном направлении.

UM

US Standard

Construction

 RADIAL

Machinery

Сельское хозяйство: вездеход

Version	STANDARD
Type	TL
Tyre Size	AT 27 X 11 R 14
LI/SS	56 N

Dimensions US Standard

Usa code	94052622
Section Width (inch)	11
Overall Diameter (inch)	27.6
Static Loaded Radius (inch)	12.5
Rolling Circumference (inch)	82.3
Rim Rec	9.00
Star Rating	***
ECE	E11-75R-005097

Load capacity (lbs)

mph / psi	7
87	495

Printed on 27.04.2024 5:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..