

SKID POWER (CHEVRON) - Технические спецификации



Description

Шины SKID POWER (CHEVRON) специально разработаны для погрузчиков с бортовым поворотом, используемых в строительных работах. Они отличаются превосходными тяговыми характеристиками и улучшенной самоочистительной способностью. SKID POWER (CHEVRON) имеют превосходные показатели устойчивости к порезам и разрывам и особенно подходят для эксплуатации на рыхлых покрытиях.

UM

International Standard

Construction

 BIAS

Machinery

Производство: Мини-погрузчик с бортовым поворотом

Version	IMPLEMENT
Type	TL
Tyre Size	7.00 - 15
LI/SS	106 A8

Dimensions International Standard

Ply Rating	6
Section Width (mm)	203
Overall Diameter (mm)	762
Static Loaded Radius (mm)	347
Rolling Circumference (mm)	2295
Rim Rec	5.50 F
Rim Alt	6 LB
ECE	E11-106R-003583

Load capacity (Kg)

km/h / bar	4.10
40	950

Printed on 26.04.2024 11:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..