

## SKID POWER HD (A) - Технические спецификации



### **Description**

Шины SKID POWER HD (A) разработаны для погрузчиков с бортовым поворотом, используемых в строительных работах. Очень глубокий рисунок протектора и защита боковин помогают предотвратить порезы и разрывы шины и обеспечивают ее исключительную долговечность. SKID POWER HD (A) идеально подходят для эксплуатации на рыхлых покрытиях в условиях больших нагрузок.

### **UM**

**US Standard** 

### Construction



# Machinery

Производство: Мини-погрузчик с бортовым поворотом

Version	STANDARD
Туре	TL
Tyre Size	31 X 15.5 - 15
LI/SS	139 A2/121 B

### **Dimensions US Standard**

Usa code	94065226
Ply Rating	10
Section Width (inch)	15.7
Overall Diameter (inch)	31.1
Static Loaded Radius (inch)	14.9
Rolling Circumference (inch)	94.9
Rim Rec	13 LB
ECE	E11-106R-003571

### Load capacity (lbs)

mph / psi	61
5	5410
10	4330
30	3280

#### Printed on 26.04.2024 8:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..