

SKID POWER HD (A) - Технические спецификации



Description

Шины SKID POWER HD (A) разработаны для погрузчиков с бортовым поворотом, используемых в строительных работах. Очень глубокий рисунок протектора и защита боковин помогают предотвратить порезы и разрывы шины и обеспечивают ее исключительную долговечность. SKID POWER HD (A) идеально подходят для эксплуатации на рыхлых покрытиях в условиях больших нагрузок.

UM

International Standard

Construction

 BIAS

Machinery

Производство: Мини-погрузчик с бортовым поворотом

Version	STANDARD
Type	TL
Tyre Size	31 X 15.5 - 15

Dimensions International Standard

Ply Rating	8
Section Width (mm)	400
Overall Diameter (mm)	790
Static Loaded Radius (mm)	378
Rolling Circumference (mm)	2411
Rim Rec	13 LB

Load capacity (Kg)

km/h / bar	3.10
15	1655
50	1255

Printed on 26.04.2024 6:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..