

SKID POWER HD (B) - Технические спецификации



Description

Шины SKID POWER HD (B) разработаны для погрузчиков с бортовым поворотом, используемых в строительных работах. Очень глубокий рисунок протектора и защита боковин помогают предотвратить порезы и разрывы шины и обеспечивают ее исключительную долговечность. SKID POWER HD (B) идеально подходят для эксплуатации на рыхлых покрытиях в условиях больших нагрузок.

UM

US Standard

Construction

 BIAS

Machinery

Производство: Мини-погрузчик с бортовым поворотом

| | |
|-----------|---------------|
| Version | IMPLEMENT |
| Type | TL |
| Tyre Size | 18 X 8.5 - 10 |
| LI/SS | 82 A8 |

Dimensions US Standard

| | |
|------------------------------|-------------------------------|
| Usa code | 94055937 |
| Ply Rating | 8 |
| Section Width (inch) | 8.1 |
| Overall Diameter (inch) | 18.3 |
| Static Loaded Radius (inch) | 8.4 |
| Rolling Circumference (inch) | 54 |
| Rim Rec | 7.00 I - 55 ; I - 70 ; I - 90 |
| ECE | E11-106R-003536 |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 44 |
| 25 | 1047 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 11.02.2025 12:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..