

## SKID POWER SK - Технические спецификации



### Description

Шины SKID POWER SK специально разработаны для погрузчиков с бортовым поворотом, используемых в строительных работах. Защита боковин и обода диска, а также глубокий рисунок протектора предусмотрены для обеспечения долгого срока службы шин.

### UM

US Standard

### Construction

 BIAS

### Machinery

Производство: Мини-погрузчик с бортовым поворотом

Version	STANDARD
Type	TL
Tyre Size	12 - 16.5

## Dimensions US Standard

Usa code	94017263
Ply Rating	12
Section Width (inch)	12.3
Overall Diameter (inch)	32.5
Static Loaded Radius (inch)	14.8
Rolling Circumference (inch)	95.8
Rim Rec	9.75

## Load capacity (lbs)

	mph / psi	80
	5	6320
	10	4990
	15	4610

Printed on 27.04.2024 11:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..