SKID POWER - Технические спецификации

Description

Шины SKID POWER разработаны для погрузчиков с бортовым поворотом, используемых в строительных работах. Они отличаются превосходными тяговыми характеристиками и улучшенной самоочистительной способностью. Очень глубокий рисунок протектора и дополнительная защита боковин помогают предотвратить порезы и разрывы шины и обеспечивают ее исключительную долговечность. Шины SKID POWER идеально подходят для эксплуатации на рыхлых покрытиях.

UM

US Standard

Construction

BIAS

Machinery

Производство: Мини-погрузчик с бортовым поворотом

Version	IMPLEMENT
Type	TL
Tyre Size	10 - 16.5
LI/SS	116 A8

Dimensions US Standard

Usa code	94055661
Ply Rating	8
Section Width (inch)	10
Overall Diameter (inch)	30.5
Static Loaded Radius (inch)	14
Rolling Circumference (inch)	90
Rim Rec	8.25
ECE	E11-106R-003534

Load capacity (lbs)

mph / psi	60
25	2755

Printed on 25.04.2024 8:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..