

SL 441 - Технические спецификации



Description

ST 441 — это дорожные шины для сельскохозяйственной техники и прицепов, используемых для обработки почвы и грузовых перевозок. Шины SL 441 были разработаны для обеспечения высокой грузоподъемности и долгого срока службы.

UM

US Standard

Construction



₩ BIAS

Machinery

Сельское хозяйство: Сельскохозяйственное оборудование • Прицеп

Version	STANDARD
Туре	π
Tyre Size	200/60 - 14.5
LI/SS FREE ROLLING	106 A8

Dimensions US Standard

Usa code	94011087
Ply Rating	10
Section Width (inch)	8.3
Overall Diameter (inch)	24
Static Loaded Radius (inch)	10.9
Rolling Circumference (inch)	70.3
Rim Rec	AG 6.75

Load capacity (lbs)

mph / psi	73
5 FR	2930
15 FR	2490
20 FR	2350
25 FR	2090

Printed on 25.04.2024 10:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..