

SM 54 IND-4S - Технические спецификации



Description

Шины SM 54 IND-4S специально разработаны для установки на штабелёры обработки порожних контейнеров и контейнерные погрузчики в интермодальных грузоперевозках и логистике. Эти шины гарантируют высокую стабильность в режиме подъема, а их глубокий и гладкий рисунок протекторов надежно защищает от порезов и продлевает срок службы.

UM

International Standard

Construction

 BIAS

Machinery

Производство: Контейнерный погрузчик

Version	INDUSTRIAL
Type	TL
Tyre Size	16.00 - 25

Dimensions International Standard

Ply Rating	28
Overall Width (mm)	430
Overall Diameter (mm)	1470
Static Loaded Radius (mm)	676
Rolling Circumference (mm)	4354
Rim Rec	11.25/2.0
Rim Alt	13.00/2.0
TRA Code	L4S

Load capacity (Kg)

km/h / bar	9.00
10	15525

Printed on 25.04.2024 18:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..