

SM 55 IND-5S - Технические спецификации



Description

Шины SM 55 IND-5S специально разработаны для контейнерных погрузчиков и укладчиков. Специальная износостойкая резиновая смесь протектора продлевает срок службы шины при эксплуатации на асфальтовых или бетонных покрытиях и обеспечивает превосходную устойчивость транспортного средства при подъеме грузов.

UM

International Standard

Construction

 BIAS

Machinery

Производство: Погрузчик контейнеров

Version	PORT SPECIAL
Type	TL
Tyre Size	18.00 - 25

Dimensions International Standard

Ply Rating	40
Overall Width (mm)	517
Overall Diameter (mm)	1665
Static Loaded Radius (mm)	765
Rolling Circumference (mm)	5118
Rim Rec	13.00/2.5
Rim Alt	15.00/2.5
TRA Code	IND5

Load capacity (Kg)

km/h / bar	10.00
10	22950

Printed on 26.04.2024 6:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..