# **SNOW GRIP -** Технические спецификации

## Description

Шина SNOW GRIP спроектирована под эксплуатацию на вилочных погрузчиках в условиях низких температур окружающего воздуха. Для уникального рисунка протектора характерно большое количество кромок сцепления, обеспечивающих превосходную тягу как на рыхлом, так и на уплотненном снегу. Результатом этого выступают отличные характеристики прохождения поворотов и торможения на обледенелых и заснеженных покрытиях. Конструкция с двойным бортом, очень прочный каркас и усиленные боковины служат залогом повышенной грузоподъемности, великолепной устойчивости и управляемости в режиме подъема грузов, а также долгого срока службы.

## UM

International Standard

## Construction

BIAS

## Machinery

Производство: Вилочный погрузчик

| | |
|---|---|
| **Version** | STANDARD |
| **Type** | TT |
| **Tyre Size** | 7.50 - 16 |
| **LI/SS** | 131 A2 |

## Dimensions International Standard

| | |
|---|---|
| **Ply Rating** | 12 |
| **Section Width (mm)** | 210 |
| **Overall Diameter (mm)** | 810 |
| **Rim Rec** | 6.0 |

## Load capacity (Kg)

| km/h / bar | 5.0 |
|---|---|
| **10** | 1950 |

Printed on 27.04.2024 1:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..