SNOW - RIDE (A) - Технические спецификации

Description

SNOW-RIDE — это зимняя шина для компактных погрузчиков и погрузчиков с бортовым поворотом, выполняющих коммунальные и технические работы. Они имеют превосходные тяговые характеристики и идеально подходят для эксплуатации на льду или снежном покрытии. Специальный рисунок протектора препятствует проскальзыванию шины и обеспечивает длительный срок службы.

UM

International Standard

Construction

BIAS

Machinery

Сельское хозяйство: Компактный погрузчик
Производство: Мини-погрузчик с бортовым поворотом

Version	STANDARD
Type	TL
Tyre Size	12 - 16.5

Dimensions International Standard

Ply Rating	6
Section Width (mm)	305
Overall Diameter (mm)	835
Static Loaded Radius (mm)	379
Rolling Circumference (mm)	2505
Rim Rec	9.75
Rim Alt	-

Load capacity (Kg)

km/h / bar	2.80
10	1915

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12.10.2024 4:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..