

SNOW - RIDE (B) - Технические спецификации

Description

Шины SNOW-RIDE особенно подходят для погрузчиков и бульдозеров, эксплуатируемых на дорогах в зимних условиях. Они имеют превосходные тяговые характеристики и идеально подходят для эксплуатации на льду или снежном покрытии. Специальный рисунок протектора помогает предотвратить проскальзывание.

UM

International Standard

Construction

 BIAS

Machinery

Производство: Бульдозер • Погрузчик



Version	STANDARD
Type	TL
Tyre Size	20.5 - 25

Dimensions International Standard

Ply Rating	16
Section Width (mm)	537
Overall Diameter (mm)	1492
Static Loaded Radius (mm)	652
Rolling Circumference (mm)	4423
Rim Rec	17.00/2.0
Rim Alt	17.00/1.7
TRA Code	L2

Load capacity (Kg)

km/h / bar	3.50
10	8250

Printed on 26.04.2024 6:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..