

ST 180 - Технические спецификации



Description

ST 180 — это шина для прицепов и сельскохозяйственной техники, которые используются для грузовых перевозок. Специальный рисунок протектора с высокой износостойкостью гарантирует длительный срок службы шины. Шина ST 180 доступна в нескольких вариантах: версия с арамидным брекером обеспечивает повышенную сопротивляемость проколам, в то время как специальная версия гарантирует высокую устойчивость к порезам и разрывам.

UM

US Standard

Construction

❖ BIAS

Machinery

Сельское хозяйство: Сельскохозяйственное оборудование •
Прицеп

| | |
|-----------|----------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 6.00 - 9 |

Dimensions US Standard

| | |
|-------------------------|---------------------------------|
| Usa code | 94008827 |
| Ply Rating | 8 |
| Section Width (inch) | 6.5 |
| Overall Diameter (inch) | 21.3 |
| Rim Rec | 4.00 - I - 55 |
| Rim Alt | 4.50 - I - 55 ; I - 70 ; I - 90 |
| ECE | E4-54R-0022804 |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 85 |
| 62 | 1390 |

Printed on 26.04.2024 6:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..