

STAR TRAC - Технические спецификации



Description

STAR TRAC - это шины компании BKT для комбайнов на хлопководческих фермах, способные выдерживать высокие нагрузки. Благодаря очень глубокому рисунку протектора эти шины обеспечивают превосходную тягу при работе в полях и превосходную эффективность при дорожных перевозках. Для техники на хлопковых плантациях, где обычно растут кустарники средней высоты, требуются шины с великолепной проходимостью и низкой степенью уплотнения почвы. Помимо этих преимуществ, эти шины также обладают высоким сопротивлением проколам и другим характерным повреждениям за счет использования уникальной резиновой смеси протектора.

UM

US Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Хлопкоуборочная машина

Version	STANDARD
Type	TL
Tyre Size	DW 500/95 D 32
LI/SS	162 A8/169 A5

Dimensions US Standard

Usa code	94041404
Section Width (inch)	19.7
Overall Diameter (inch)	72.3
Static Loaded Radius (inch)	31.9
Rolling Circumference (inch)	209.6
Rim Rec	13.00 DW

Load capacity (lbs)

	mph / psi	26
	25	10470
	15	12790

Printed on 25.04.2024 21:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..