

SUPER GRADER - Технические спецификации



Description

SUPER GRADER (G-2) - это диагональные шины, разработанные специально для грейдеров. Они демонстрируют отличные тяговые характеристики и самоочистительную способность. Протектор SUPER GRADER изготовлен из уникальной резиновой смеси, которая гарантирует долгий срок службы таких шин и позволяет эксплуатировать их в условиях высоких нагрузок.

UM

US Standard

Construction

 BIAS

Machinery

Производство: Грейдер

Version	STANDARD
Type	TL
Tyre Size	13.00 - 24

Dimensions US Standard

Usa code	94014477
Ply Rating	12
Overall Width (inch)	13.4
Overall Diameter (inch)	50.2
Static Loaded Radius (inch)	23.1
Rolling Circumference (inch)	149.6
Rim Rec	8.00 TG SDC
Rim Alt	9.00/1.5 (DC) ; 10.00/VA SDC
TRA Code	G2

Load capacity (lbs)

mph / psi	44
25	6000

Printed on 25.04.2024 19:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..