

SUPER SAND - Технические спецификации



Description

Шины SUPER SAND в основном предназначены для прицепов, работающих на песчаных покрытиях в жарких погодных условиях. Они отличаются высокой проходимостью и идеально подойдут для любой техники, от которой требуется высокий уровень управляемости.

UM

International Standard

Construction

 BIAS

Machinery

Производство: Прицеп

Version	STANDARD
Type	TT
Tyre Size	14.00 - 20

Dimensions International Standard

Ply Rating	18
Section Width (mm)	385
Overall Diameter (mm)	1225
Rim Rec	10.00 V
Rim Alt	10.00 W

Load capacity (Kg)

km/h / bar	5.85
65 LS	3965
65 LD	3490

Printed on 26.04.2024 15:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..