

SURE TRAX HD - Технические спецификации



Description

SURE TRAX HD - это шины с блочным рисунком протектора для погрузчиков с бортовым поворотом, используемых для строительных работ. Шины с отличной защитой обода диска отличаются высочайшей устойчивостью к порезам и разрывам. SURE TRAX HD идеально подходят для эксплуатации на твердых покрытиях в условиях больших нагрузок.

UM

International Standard

Construction

 BIAS

Machinery

Производство: Мини-погрузчик с бортовым поворотом

Version	INDUSTRIAL
Type	TL
Tyre Size	33 X 15.5 - 16.5
LI/SS	151 A2

Dimensions International Standard

Ply Rating	14
Section Width (mm)	400
Overall Diameter (mm)	855
Rim Rec	13.00
ECE	E11-106R-006012

Load capacity (Kg)

km/h / bar	4.80
10	3450
15	2725
25	2520

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 13.05.2025 10:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..