

## TR 117 - Загрузить лист технических данных



### Description

Шины TR 117 идеально подходят для поворотных оросительных установок. Специальный рисунок протектора характеризуется выдающимися тяговыми свойствами и способностью к самоочищению.

### UM

US Standard

### Construction

 BIAS

### Machinery

Сельское хозяйство: Дождевальная машина

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
11.2 - 24	STANDARD	94028498	R1	98 A8	4	W 10	W 9	11.2	42.9	20	126.2	TT	E4-106R-001966
11.2 - 24	STANDARD	94029044	R1	98 A8	4	W 10	W 9	11.2	42.9	20	126.2	TL	E4-106R-001966
11.2 - 24	STANDARD	94028368	R1	106 A8	6	W 10	W 9	11.2	42.9	20	126.2	TT	E4-106R-001967
11.2 - 24	STANDARD	94029082	R1	106 A8	6	W 10	W 9	11.2	42.9	20	126.2	TL	E4-106R-001967
13.6 - 24	STANDARD	94046805	R1	115 A8	6	W 12	W 11	13.8	46.7	21.3	141.4	TT	E11-106R-004419
13.6 - 24	STANDARD	94047406	R1	115 A8	6	W 12	W 11	13.8	46.7	21.3	141.4	TL	E11-106R-004419
14.9 - 24	HD	94048410	R1	124 A8	8	W 13	W 11 ; W 12	14.9	49	22.6	144.1	TL	E11-106R-004633
14.9 - 24	STANDARD	94002993	R1	109 A8	4	W 13	W 11 ; W 12	14.9	49	22.6	144.1	TT	E4-106R-002026
14.9 - 24	STANDARD	94029051	R1	109 A8	4	W 13	W 11 ; W 12	14.9	49	22.6	144.1	TL	E4-106R-002026
14.9 - 24	STANDARD	94003006	R1	119 A8	6	W 13	W 11 ; W 12	14.9	49	22.6	144.1	TT	E4-106R-002027
14.9 - 24	STANDARD	94003013	R1	119 A8	6	W 13	W 11 ; W 12	14.9	49	22.6	144.1	TL	E4-106R-002027
14.9 - 24	STANDARD	94003020	R1	124 A8	8	W 13	W 11 ; W 12	14.9	49	22.6	144.1	TT	E11-106R-004530
14.9 - 24	STANDARD	94031429	R1	124 A8	8	W 13	W 11 ; W 12	14.9	49	22.6	144.1	TL	E11-106R-004530
11.2 - 38	STANDARD	94028801	R1	106 A8	4	W 10	W 9	11.2	56.9	26.6	173.2	TT	E4-106R-002747
11.2 - 38	STANDARD	94030408	R1	106 A8	4	W 10	W 9	11.2	56.9	26.6	173.2	TL	E4-106R-002747
11.2 - 38	STANDARD	94030415	R1	113 A8	6	W 10	W 9	11.2	56.9	26.6	173.2	TT	E4-106R-002748
11.2 - 38	STANDARD	94031368	R1	113 A8	6	W 10	W 9	11.2	56.9	26.6	173.2	TL	E4-106R-002748

Printed on 13.04.2024 0:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..