

## TR 126 - Технические спецификации



### Description

Шины TR 126 разработаны для небольших тракторов, используемых для обработки почвы. Глубокие грунтозацепы и специальный рисунок протектора обеспечивают превосходную тягу, великолепную грузоподъемность и выдающиеся свойства самоочистки, а также высокую эффективность в любых условиях эксплуатации.

### UM

US Standard

### Construction

 BIAS

### Machinery

Сельское хозяйство: Мини-трактор

Version	STANDARD
Type	TT
Tyre Size	7 - 14
LI/SS	92 A8

## Dimensions US Standard

Usa code	94052639
Ply Rating	8
Section Width (inch)	6.7
Overall Diameter (inch)	27.2
Static Loaded Radius (inch)	12.6
Rolling Circumference (inch)	81.5
Rim Rec	5 JA ; 5 KB
ECE	E11-106R-005233
TRA Code	R1

## Load capacity (lbs)

mph / psi	58
25	1390

Printed on 27.04.2024 19:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..