

## TR 135 - Технические спецификации



### Description

Шины TR 135 отлично подходят для тракторов, используемых при обработке почвы. Усиленный каркас и специальная резиновая смесь, устойчивая к порезам и разрывам, обеспечивают увеличенный срок службы. Высокая тяга, самоочистение и грузоподъемность являются главными преимуществами, которые позволяют использовать шины TR 135 даже на самых сложных покрытиях.

### UM

US Standard

### Construction

 BIAS

### Machinery

Сельское хозяйство: Трактор-тягач  
Производство: Прицеп

|           |           |
|-----------|-----------|
| Version   | STANDARD  |
| Type      | TT        |
| Tyre Size | 13.6 - 28 |
| LI/SS     | 122 A8    |

## Dimensions US Standard

|                              |                |
|------------------------------|----------------|
| Usa code                     | 94003341       |
| Ply Rating                   | 8              |
| Section Width (inch)         | 13.6           |
| Overall Diameter (inch)      | 51.6           |
| Static Loaded Radius (inch)  | 23.9           |
| Rolling Circumference (inch) | 153.9          |
| Rim Rec                      | W 12           |
| Rim Alt                      | W 11           |
| ECE                          | E4-106R-002749 |
| TRA Code                     | R1             |

## Load capacity (lbs)

|           |      |
|-----------|------|
| mph / psi | 28   |
| 25        | 3300 |

Printed on 10.08.2024 3:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..