

TR 135 - Технические спецификации



Description

Шины TR 135 отлично подходят для тракторов, используемых при обработке почвы. Усиленный каркас и специальная резиновая смесь, устойчивая к порезам и разрывам, обеспечивают увеличенный срок службы. Высокая тяга, самоочищение и грузоподъемность являются главными преимуществами, которые позволяют использовать шины TR 135 даже на самых сложных покрытиях.

UM

International Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Трактор-тягач
Производство: Прицеп

Version	STANDARD
Type	TT
Tyre Size	23.1 - 30
LI/SS	146 A6

Dimensions International Standard

Ply Rating	8
Section Width (mm)	600
Overall Diameter (mm)	1700
Static Loaded Radius (mm)	773
Rolling Circumference (mm)	5217
Rim Rec	DW 20 B ; DW 20 A
ECE	E4-106R-002303
TRA Code	R1

Load capacity (Kg)

km/h / bar	1.10
30	3000

Printed on 22.04.2024 20:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..