

TR 135 - Технические спецификации



Description

Шины TR 135 отлично подходят для тракторов, используемых при обработке почвы. Усиленный каркас и специальная резиновая смесь, устойчивая к порезам и разрывам, обеспечивают увеличенный срок службы. Высокая тяга, самоочистение и грузоподъемность являются главными преимуществами, которые позволяют использовать шины TR 135 даже на самых сложных покрытиях.

UM

US Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Трактор-тягач
Производство: Прицеп

Version	STANDARD
Type	TT
Tyre Size	23.1 - 34
LI/SS	150 A8

Dimensions US Standard

Usa code	94034222
Ply Rating	10
Section Width (inch)	23
Overall Diameter (inch)	71.3
Static Loaded Radius (inch)	32.8
Rolling Circumference (inch)	209.5
Rim Rec	DW 20 B ; DW 20 A
ECE	E4-106R-002831
TRA Code	R1

Load capacity (lbs)

mph / psi	20
25	7400

Printed on 22.04.2024 21:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..