

## TR 135 - Технические спецификации



### Description

Шины TR 135 отлично подходят для тракторов, используемых при обработке почвы. Усиленный каркас и специальная резиновая смесь, устойчивая к порезам и разрывам, обеспечивают увеличенный срок службы. Высокая тяга, самоочистение и грузоподъемность являются главными преимуществами, которые позволяют использовать шины TR 135 даже на самых сложных покрытиях.

### UM

International Standard

### Construction

 BIAS

### Machinery

Сельское хозяйство: Трактор-тягач

Производство: Прицеп

Version	STANDARD
Type	TT
Tyre Size	8.3 - 28
LI/SS	108 A6

## Dimensions International Standard

Ply Rating	8
Section Width (mm)	213
Overall Diameter (mm)	1104
Static Loaded Radius (mm)	519
Rolling Circumference (mm)	3347
Rim Rec	W 7
Rim Alt	W 6
ECE	E4-106R-001974
TRA Code	R1

## Load capacity (Kg)

km/h / bar	3.20
30	1000

Printed on 16.04.2024 6:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..